

WNMP 060404 NN LT 10 & LT 1000

Material Group	Gr. N°	VDI Group	Material Examples*	Hardness	D.O.C. [mm]		Feed [mm/rev]		Amax [mm²]	V _c [m/min]		Optimal cutting conditions		
					min	max	min	max		min	max	D.O.C.	Feed	V _c
Steel	Non-alloyed	1	1 C35, Ck45, 1020, 1045, 1060, 28Mn6	125 HB	0.2	3.0	0.11	0.23	0.60	180	330	2.0	0.18	300
		2		190 HB		2.5		0.22	0.52		280			260
		3		250 HB		2.5		0.20	0.48		250			240
	Low alloyed	2	6 42CrMo4, St50, 4,6 Ck60, 4140, 4340, 5,7 100Cr6	180 HB	0.2	2.5	0.10	0.20	0.50	120	280	2.0	0.15	260
				230 HB		2.5		0.20	0.48		250			240
				280 HB		2.0		0.18	0.40		210			200
				350 HB		2.0		0.18	0.36		180			180
	High alloyed	3	10 X40CrMoV5, 10 H13, M42, D3, 11 S6-5-2, 12Ni19	220 HB	0.2	2.5	0.09	0.18	0.40	70	190	2.0	0.12	180
				280 HB		2.5		0.16	0.40		150			140
				320 HB		2.0		0.14	0.32		130			120
				350 HB		2.0		0.14	0.26		110			110
Stainless Steel	Austenitic	4	14 304, 316, 14 X5CrNi18-9	180 HB	0.2	2.5	0.10	0.18	0.32	170	270	2.0	0.12	260
				240 HB		2.5		0.18	0.26	160	220			210
	Duplex	5	14 X2CrNiN23-4, 14 S31500	290 HB	0.2	2.0	0.09	0.14	0.20	80	150	2.0	0.12	140
				310 HB		2.0		0.14	0.20	70	140			
	Ferritic & Martensitic	6	12 410, X6Cr17, 13 17-4 PH, 430	200 HB	0.2	2.5	0.10	0.18	0.32	170	250	2.0	0.15	240
				42 HRc		2.0		0.16	0.26	120	190			180
Cast Iron	Grey	7	15 GG20, GG40, 16 EN-GJL-250, 16 No30B	150 HB	0.2	3.0	0.08	0.20	0.64	170	250	2.0	0.18	240
				200 HB		3.0		0.20	0.60	160	230			220
				250 HB		3.0		0.20	0.60	150	210			200
	Malleable & Nodular	8	17,19 GGG40, GGG70, 17,19 50005	150 HB	0.2	2.5	0.08	0.18	0.48	120	250	2.0	0.15	240
				200 HB		2.5		0.18	0.40	120	230			220
				250 HB		2.5		0.18	0.40	120	190			180
High Temp. Alloys	Fe, Ni & Co based	9	31,32 Incoloy 800	240 HB	0.2	2.0	0.09	0.15	0.26	25	50	2.0	0.12	40
			33 Inconel 700	250 HB		2.0		0.15	0.26	25	50			40
			34 Stellite 21	350 HB		2.0		0.15	0.26	23	45			35
	Ti based	10	36 TiAl6V4	-	0.2	2.0	0.09	0.16	0.32	45	65	2.0	0.15	60
			37 T40	-		2.0		0.14	0.26	35	60			50
Hardened Mat.	Steel	11	38 X100CrMo13, 38 440C, 38 G-X260NiCr42	45 HRc	0.2	1.8	0.05	0.12	0.20	50	100	1.5	0.11	90
				50 HRc		1.5		0.10	0.17	40	90	1.2	0.09	80
				55 HRc		1.4		0.09	0.13	40	80	1.0	0.07	70
	Chilled Cast Iron		40 Ni-Hard 2	400 HB	0.2	1.6	0.05	0.12	0.17	40	60	1.2	0.11	50
	White Cast Iron		41 G-X300CrMo15	55 HRc	0.2	1.4	0.05	0.09	0.13	30	50	1.0	0.07	40
NF	Al (>8%Si)	12	25 AlSi12	130 HB	0.2	4.0	0.10	0.30	0.70	200	400	2.0	0.20	350